



## Hexagon flange nut

Steel cl. 8 - cl. 10 - cl. 12  
Stainless steel A2-70

DIN 6923  
ISO 4161

**Designation :**

hexagon flange nut,  $\varnothing$  12 mm, normal metric thread = DIN 6923 M12

| d   | D    | S  | e     | m  | h    | Weight in<br>kg per<br>1000p | Packaging |
|-----|------|----|-------|----|------|------------------------------|-----------|
| M5  | 11,8 | 8  | 8,74  | 5  | 2,2  |                              |           |
| M6  | 14,2 | 10 | 11,05 | 6  | 3,1  |                              |           |
| M8  | 17,9 | 13 | 14,38 | 8  | 4,5  |                              |           |
| M10 | 21,8 | 15 | 16,64 | 10 | 5,5  |                              |           |
| M12 | 26   | 18 | 20,03 | 12 | 6,7  |                              |           |
| M14 | 29,9 | 21 | 23,36 | 14 | 7,8  |                              |           |
| M16 | 34,5 | 24 | 26,75 | 16 | 9    |                              |           |
| M20 | 42,8 | 30 | 32,95 | 20 | 11,1 |                              |           |

**Execution :**

A (formerly m) as per DIN ISO 4759/1

**Thread :**

according to DIN 13/12 & DIN 13/15 - tolerance class 6H.